

Test Report

No.: SDHL1707015714FT Date:

Date: Aug.03, 2017

Page 1 of 4

FOSHAN ZHONG MENG SHENG YE OFFICE FURNITURE CO., LTD. NO.6, GAOJIAO NANFANG INDUSTRIAL AREA, LONGJIANG TOWN, SHUNDE DISTRICT, FOSHAN CITY, GUANGDONG PROVINCE, CHINA.

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description	:	OFFICE CHAIR
Style / Item No.	:	ZM-411BL-2
Sample Receiving Date	:	Jul.28, 2017
Test Performing Date	:	Jul.28, 2017 to Aug.03, 2017

Test Result Summary

Test(s) Requested	Result(s)
Clause 5, 7, 12 and 13 of ANSI/BIFMA X5.1-2017 (Type I, III)	PASS
Summary:	
1. For further details, please refer to the following page(s).	

Signed for and on behalf of Shunde Branch SGS-CSTC Co., Ltd.

Caming Fan Approved signatory





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is est report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@gs.com

1/f;f⁴Building.European Industrial Park/No.1 Shumle South Rived.Wustra Section.Datiang Town,Shunde.Fisstan,Guaragdong.China 528333 tt (86-757)22805888 ft (86-757)22805885 www.sgsgroup.com.cn 中国・广东・佛山市順徳区大良街道办事处五沙颇和南路1号欧洲工业园一号厂房首层邮编: 528333 tt (86-757)22805888 ft (86-757)22805888 e sgs.china@sgs.com



Test Report

No.: SDHL1707015714FT

Date: Aug.03, 2017

TESTS AND RESULTS

Test Conducted:

Clause 5, 7, 12 and 13 of ANSI/BIFMA X5.1-2017 General-Purpose Office Chairs – Tests.

No. of Sample:

1 piece (Sample 1). For more sample information and pictures, please refer to the following page.

Chair Type: Type I, III.

Test and Requirements	Test Results			
5 Backrest Strength Test - Static - Type I and II				
5.4.1 Functional Load There shall be no loss of serviceability to the chair when 667 N (150 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 70 degrees \pm 10 degrees to the plane of the backrest. The force is not intended to be maintained at 70 degrees \pm 10 degrees throughout the loading of the backrest.	PASS			
5.4.2 Proof Load There shall be no sudden and major change in the structural integrity of the chair, loss of serviceability is acceptable, when 1001 N (225 lbf.) is applied to the backrest at the specified position for one (1) minute. With the backrest at its back stop position, apply a force that is initially 70 degrees \pm 10 degrees to the plane of the backrest. The force is not intended to be maintained at 70 degrees \pm 10 degrees throughout the loading of the backrest.	PASS			
7 Drop Test - Dynamic				
There shall be no loss of serviceability when a test bag weighing 102 kg (225 lb.) is free fell from 152 mm (6 in.) above the uncompressed seat to the specified position on seat. Remove the bag, and set height to its lowest position and repeat the test for chairs with seat height adjustment features.	PASS			
7.4.2 Proof Load Test				
There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable when a test bag weighing 136 kg (300 lb.) is free fell from 152 mm (6 in.) above the uncompressed seat to the specified position on seat. Remove the bag, and set height to its lowest position and repeat the test for chairs with seat height adjustment features.	PASS			
12 Arm Strength Test - Vertical - Static				
12.4.1 Functional Load Apply an initially vertical pull force of 750N (169lbs.) to the load adapter which is 127 mm (5 in.) long and at least as wide as the width of the arm shall be attached to the top of the arm rest structure such that the load will be applied at the apparent weakest point that is forward of the chair backrest, for one (1) minute. There shall be no loss of serviceability. For a height adjustable arm, failure to hold its height adjustment position to within 6 mm (0.25 in.) from its original set position as the result of the loading is considered a loss of serviceability.	PASS			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format document, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1作,1⁴BuildingEuropean Industrial Park/No.1 Shunde South Road, Wustra Section, Datarag Town, Shunde, Fissten, Guargdong, China 528333 tt (86-757) 22805888 ft (86-757) 228058858 www.sgsgroup.com.cn 中国・广东・佛山市順徳区大良街道办事处五沙颇和南路1号歌洲工业园一号厂房首层邮编: 528333 tt (86-757) 22805888 ft (86-757) 22805858 e sgs.china@sgs.com



Test Report

No.: SDHL1707015714FT

Date: Aug.03, 2017

Page 3 of 4

Test and Requirements	Test Results			
12.4.2 Proof Load Apply an initially vertical pull force of 1125N (253 lbs.) to the load adapter which is 127 mm (5 in.) long and at least as wide as the width of the arm shall be attached to the top of the arm rest structure such that the load will be applied at the apparent weakest point that is forward of the chair backrest, for 15 seconds. There shall be no sudden and major change in the structural integrity of the chair. For a height adjustable arm, a sudden drop in height of greater than 25 mm (1 in.) does not meet this requirement. Loss of serviceability is acceptable.	PASS			
13 Arm Strength Test - Horizontal - Static				
13.4.1 Functional Load Apply an initially horizontal pull force of 445 N (100 lbf.) to the load adapter which is a loading device or strap, not greater than 25 mm (1 in.) in horizontal width, shall be attached to the arm so that the load is initially applied horizontally to the armrest structure at the apparent weakest point (for armrests that pivot in the horizontal plane, apply the load at the pivot point), for one (1) minute in the outward direction. A functional load applied once shall cause no loss of serviceability.	PASS			
13.4.2 Proof Load Apply an initially horizontal pull force of 667 N (150 lbf.) to the load adapter which is a loading device or strap, not greater than 25 mm (1 in.) in horizontal width, shall be attached to the arm so that the load is initially applied horizontally to the armrest structure at the apparent weakest point (for armrests that pivot in the horizontal plane, apply the load at the pivot point), for 15 seconds in the outward direction. A proof load applied once shall cause no sudden and major change in the structural integrity of the unit. Loss of serviceability is acceptable.	PASS			

Remark:

1. For the sample information and pictures, please refer to the following page.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@gs.com

1作,f⁴BuildingEuropean Industrial Park,Mo.1Shunde South Road,Wustra Section,Datang Town,Shunde,Fristin,Guargdong,China 528333 tt (86-757)22805888 ft (86-757)228058858 www.sgsgroup.com.cn 中国・广东・佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层邮编: 528333 tt (86-757)22805888 ft (86-757)228058858 e sgs.china@sgs.com



Test ReportNo.: SDHL1707015714FTDate: Aug.03, 2017Page 4 of 4

SAMPLE INFORMATION AND PICTURES

Weight: 19.95 kg

Overall Dimensions: 710 mm L x 685 mm W x 965~1075 mm H

Other Dimensions: Base radius, 330 mm

Sample as Received



View 3

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Condit

View 4

1/f;f⁴Building.European Industrial Park/No.1 Shumhe South Road, Wusha Section, Dalarag Town, Shunde Foshan, Guaragdong, China 528333 t (86-757)22805888 f (86-757)22805858 www.sgsgroup.com.cn 中国・广东・佛山市順徳区大良街道办事处五沙版和南路1号欧洲工业园一号厂房首层邮编: 528333 t (86-757)22805888 f (86-757)22805858 e sgs.china@sgs.com